

ST-8430D/ST-8438D

电子套结机
电子钉扣机

Electronic Bartacking Machine
Electronic Button Sewing Machine

高速缝纫且线迹美观，实现了世界上最快的循环时间。
实现了优良的缝纫品质和高生产效率。

Attractive seams at high speeds and the world's fastest cycle time.
Combining high quality sewing and high productivity.



机器特征

- 1、循环时间世界最快，生产效率具有压倒性优势。
- 2、完全按照缝制数据进行高质量缝纫。
- 3、实现了低张力缝制和广泛的可缝性能。
- 4、切线后无需进行再处理。
- 5、可防止缝纫开始时易出现的脱线、鸟巢状及缝线污迹。
- 6、清洁缝制，强大的机针贯穿力，采用CF卡。
- 7、低噪音、低振动、电耗低、经济实用。
- 8、缝制区域40x30mm。



Features

1. Overwhelmingly superior productivity with the world's fastest cycle time.
2. High quality sewing faithfully following the sewing data.
3. Realization of wide ranging sewing capabilities and low tension sewing.
4. Follow-up processing unnecessary after thread trimming.
5. Prevents thread cast-off, bird's nests, and stains on the thread at the beginning of the sewing operation.
6. Clean sewing, powerful needle penetration force, adoption of compact flash cards.
7. Low noise and low vibration, because of its low power consumption, it is economical.
8. Sewing area 40 x 30 mm.



ST-8430D



★



★



★



★



★



★



★



★



★



★



3200



技术参数 Technica parameter

| 用途/Application | ST-8430D | | | | | ST-8438D |
|----------------|----------------------|----|--------------------|----------------------------|------------------------------|------------------------|
| | 01 | 02 | 05 | 06 | 07 | |
| | 电子套结机 Bar tacking | | 裤攀打结机 Belt loop | 电子拼接橡胶筋机 Elastic stitch | 针织电子套结机 Knitted materials | 电子钉扣机 Button Sewing |

| | | | |
|--------------------------------|--|----------------------------|---|
| 线迹样式 Stitch formation | 单针平缝 Single needle lock stitch | 压脚上升量 Work clamp height | 最大17mm 17 mm Max. |
| 缝纫速度 Sewing speed | 3200转/分 3200rpm | 使用旋梭 Rotary hook | 半回转标准旋 Shuttle hook |
| 缝制区域(X-Y) Sewing area (X-Y) | 最大40 × 30mm Max. 40 × 30 mm | 扫线装置 Thread wiper | 标准装备 Standard equipment |
| 送布方式 Feed mechanism | Y-θ间歇送布(脉冲马达驱动方式) Y-θ intermittent feed mechanism (pulse-motor driven mechanism) | 切线装置 Thread trimmer | 标准装备 Standard equipment |
| 针距 Stitch length | 0.05-12.7 mm | 夹线装置 Thread nipper | 标准装备 Standard equipment |
| 最大针数 Max. No. of stitches | 210,000针(包括增加针数200,000针) 210,000 stitches (including 200,000 stitches which can be added) | 重量 Weight | 56kg |
| 抬压角方式 Work clamp lifter | 脉冲马达驱动方式 Pulse motor drive system | 电源 Power source | 单相100V/220V、三相200V/220V/380V/400V Single-phase 100V, 220V Three-phase 200V, 220V, 380V, 400V 400VA |

线 可订制各种D型，O字型，30*40等各类非标压脚
we also can customized special presser foot, such as D type, O type, 30*40mm type and so on.